

Question	Answer	Marks
1(a)	time (electric) current <i>allow</i> amount of substance <i>allow</i> luminous intensity <i>any two of the above quantities, 1 mark each</i>	B2
1(b)(i)	$g = (4\pi^2 \times 1.50) / (2.48^2)$ $= 9.63 \text{ m s}^{-2}$	A1
1(b)(ii)	percentage uncertainty = $2 + (3 \times 2)$ or fraction uncertainty = $0.02 + (0.03 \times 2)$	C1
	percentage uncertainty = 8%	A1
1(b)(iii)	absolute uncertainty = 0.08×9.6 $= 0.8 \text{ m s}^{-2}$	A1

Question	Answer	Marks
2(a)	$f_0 = f_s v / (v - v_s)$ $9560 = f \times 1510 / (1510 - 4.50)$	C1
	$f = 9530 \text{ Hz}$	A1
2(b)(i)	$v^2 = u^2 + 2as$ height = $5.6^2 / (2 \times 9.81)$	C1
	$= 1.6 \text{ m}$	A1
2(b)(ii)	downward sloping straight line starting from a point on the speed axis and ending at point $(T, 0)$	B1

Question	Answer	Marks
2(b)(iii)	$(\Delta)E = mg(\Delta)h$ $= 0.45 \times 9.81 \times 1.6$	C1
	$= 7.1 \text{ J}$	A1
2(b)(iv)	air resistance increases (and weight constant)	B1
	(resultant force decreases so) acceleration decreases	B1

Question	Answer	Marks
3(a)	force $\times$ displacement in the direction of the force	B1
3(b)(i)	displacement $= 4.4 \times 30$	C1
	work done $= 140 \cos 30^\circ \times 4.4 \times 30$	C1
	$= 1.6 \times 10^4 \text{ J}$	A1
3(b)(ii)	$p = F / A$	C1
	$F = 860 - 140 \sin 30^\circ (= 790)$	C1
	$A = 790 / 2400$ $= 0.33 \text{ m}^2$	A1
3(b)(iii)	$\sigma = F / A$ or $F / \pi r^2$ or $4F / \pi d^2$	C1
	$9.6 \times 10^6 = 4 \times 140 / \pi d^2$ $d = 4.3 \times 10^{-3} \text{ m}$	A1

Question	Answer	Marks
3(c)	$E = \frac{1}{2}Fx$ or $\frac{1}{2}kx^2$ or area under graph	C1
	$(\Delta)E = \frac{1}{2} \times (140 + 210) \times 0.20 \times 10^{-3}$ or $(\Delta)E = (\frac{1}{2} \times 210 \times 0.60 \times 10^{-3}) - (\frac{1}{2} \times 140 \times 0.40 \times 10^{-3})$ or $(\Delta)E = (140 \times 0.20 \times 10^{-3}) + (\frac{1}{2} \times 0.20 \times 10^{-3} \times 70)$ or $(\Delta)E = [\frac{1}{2} \times 3.5 \times 10^5 \times (0.60 \times 10^{-3})^2] - [\frac{1}{2} \times 3.5 \times 10^5 \times (0.40 \times 10^{-3})^2]$	C1
	$\Delta E = 0.035 \text{ J}$	A1

Question	Answer	Marks
4(a)(i)	distance moved by wavefront / energy during one cycle / vibration / oscillation / period (of source) or <u>minimum</u> distance between two wavefronts or distance between two <u>adjacent</u> wavefronts	B1
4(a)(ii)	maximum displacement (of particle / point on wave)	B1
4(b)(i)	1 light / waves spread (at each slit)	B1
	2 constant phase difference (between light / waves)	B1
4(b)(ii)	$n\lambda = d \sin \theta$	C1
	$d = 3 \times 650 \times 10^{-9} / \sin 34^\circ$	C1
	$d = 3.5 \times 10^{-6} \text{ m}$	A1
4(b)(iii)	wavelength of blue light is shorter (than 650 nm / red light)	M1
	so angle (between third order diffraction maxima) decreases	A1

Question	Answer	Marks
5(a)	volt / ampere	B1
5(b)	$R = \rho L / A$	C1
	$L = (1.8 \times 0.38 \times 10^{-6}) / 9.6 \times 10^{-7}$	C1
	= 0.71 m	A1
5(c)(i)	thermal energy is dissipated in resistor Y	B1
5(c)(ii)	$V / 1.2 = 1.8 / (1.8 + 0.6)$	C1
	$V = 0.90 \text{ V}$	A1
	or	
	$I = 1.2 / (1.8 + 0.6) (= 0.50)$	(C1)
	$V = 0.50 \times 1.8$ = 0.90 V	(A1)
5(d)(i)	remain the same	B1
5(d)(ii)	decrease	B1
5(e)(i)	$1 / R = 1 / 1.8 + 1 / 3.6$ $R = 1.2 \Omega$	A1

Question	Answer	Marks
5(e)(ii)	$I = 1.2 / (1.2 + 0.60)$	C1
	$= 0.67 \text{ A}$	A1
	or	
	$V_Y = 1.2 \times 0.60 / (1.2 + 0.60) (= 0.40)$	(C1)
	$I = 0.40 / 0.60$ $= 0.67 \text{ A}$	(A1)

Question	Answer	Marks
6(a)	$E = V / d$ $d = 350 / 1.4 \times 10^4$	C1
	$= 0.025 \text{ m}$	A1
6(b)(i)	$E = F / Q$	C1
	$Q = 6.7 \times 10^{-15} / 1.4 \times 10^4 (= 4.8 \times 10^{-19} \text{ C})$ $= (4.8 \times 10^{-19} / 1.6 \times 10^{-19}) e$	C1
	$= 3.0 e$	A1
6(b)(ii)	mass $= 8.3 \times 10^{-27} / 1.66 \times 10^{-27}$ $= 5.0 \text{ u}$	A1
6(b)(iii)	number $= 5 - 3$ $= 2$	A1

Question	Answer	Marks
7(a)	made up of quarks (so) not a fundamental particle	B1
7(b)(i)	beta plus / β^+ (particle)	B1
	(electron) neutrino / $\nu_{(e)}$	B1
7(b)(ii)	kinetic energy of nucleus	B1
	gamma / γ radiation	B1

Cam E-Guide